CerchioLighting
cerchio = circle

CAPO OUT CHANDELIER
(STANDARD GRADE)


BEAM OUT



CerchioLighting
cerchio = circle

CODE: NS-LL0208

PROJECT
SPEC TYPE
NOTES





GENERAL INFORMATION:

CAPO OUT CHANDELIER - STANDARD GRADE offers a unparalleled value cost proposition in 6 standard sizes ranging from 16 to 60 inch diameters. Indirect lighting from 2700K to 4000K . Offering two standard canopy and mounting options. Housing is full aluminum construction with both standard powder coating in black or white as well as custom RAL options. Complete Collection offers optional Emergency Back up kits, Motion, Occupancy, and Light harvesting control interfaces.

OPTICS:

PMMA lenses, Anti-UV Operation

FINISHING:

Matt White, Matt Black, custom on request

BODY:

Aluminum body construction.

VOLTAGE:

110-277V

LIGHTING:

LED

LIGHTING EFFICIENCY:

≧ 70 lm/w

IP RATING:

44

APPLIANCE CLASS:

I

Contact Us:
sales@gordonbullard.com
www.cerchiolighting.com
1 877-964-4646

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.


©Bullard & Company 2024 All Rights Reserved

Updated 01/16/2024

CerchioLighting
cerchio = circle

CODE: NS-LL0208

PROJECT
SPEC TYPE
NOTES





HOW TO ORDER:

CODE

Example: NS-LL0207-D-S-D24-1-3-30W-80-27K-DIM-SW-CS

NS-LL0208

1 LIGHT DISTRIBUTION:

-D

-D	DIRECT

2 INSTALLATION TYPE:

-S

-S	Suspended

3 CIRCLE DIAMETER:

-D16	16"	**-D48**	48"
-D24	24"	**-D60**	60"
-D32	32"		
-D40	40"		

4 SIDE PROFILE HEIGHT:

-1-3

-1-3	1.3"

5 POWER AND LIGHT EMISSION:

CODE = WATTS | Ø		DIRECT LUMENS
-20W	16"	1,400 lm
-30W	24"	2,100 lm
-40W	32"	2,800 lm
-50W	40"	3,500 lm
-60W	48"	4,200 lm
-80W	60"	5,600 lm

*E.G : 40W = 40 total Watts

6 LED CRI:

-80	CRI 80
-90	CRI 90

7 SPECIFY CCT:

-27K	2700K	**-35K**	3500K
-30K	3000K	**-40K**	4000K

Contact Us:
sales@gordonbullard.com
www.cerchiolighting.com
1 877-964-4646

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.


©Bullard & Company 2024 All Rights Reserved

Updated 01/16/2024

CerchioLighting
cerchio = circle

CODE: NS-LL0208

PROJECT
SPEC TYPE
NOTES





HOW TO ORDER: CODE

8 DIMMING OPTION:

- **-STD** Non-Dimmable
- **-DIM** 1-10V

9 FIXTURE FINISH:


- **-SW** Matt White
- **-SB** Matt Black
- **-RAL** Custom RAL on request*

* E.G. : RAL = #3020

10 CANOPY OPTIONS:



CS
cable
straight



CSS
central
standard

11 ADDITIONAL FEATURES:

- **-RE** Remote Emergency
- **-OS** Occupancy Sensor
- **-DS** Daylight Sensor/Light Harvesting

* E.G. : RE = Remote Emergency

Contact Us:
sales@gordonbullard.com
www.cerchiolighting.com
1 877-964-4646


Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

©Bullard & Company 2024 All Rights Reserved


Updated 01/16/2024

12 CHANDELIER CONFIGURATIONS:


CAPO OUT circles may be ordered as separate circle pendants and/or in cluster configurations of two, three or five fixtures of various sizes, as well as custom clusters. (Consult factory for custom designs.)




C01.




C02.




C03.




C04.




C05.



C06.



C07.



C08.



C09.



C10.



C11.



C12.

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

©Bullard & Company 2024 All Rights Reserved